

# Product Data Sheet

Revised: 2018/09/25 (version 3.4)



PETRONAS

# PETRONAS Tutela Axle 500 SAE 75W-90

Designed to be the Fluid Technology Solution of choice providing improved protection for axle and final drive systems

## Description and Applications

PETRONAS Tutela Axle 500 is a premium semi synthetic axle fluid delivering optimized load carrying performances and component durability for today's axles, differentials and final drives over their standard service life. Suitable in a wide range of operating temperatures, it's recommended in transmissions requiring API GL-5.

## Benefits

PETRONAS Tutela Axle 500 protects your Business Profits and your Vehicle Availability while reducing your operating costs, through:

- **Fuel Economy** capability by **optimized transmission efficiency**:
  - o A wider operating temperature to help reduce operational energy losses.
- **Longer Axle Life** driven by:
  - o Enhanced anti-wear, Extreme Pressure (EP), anti-pitting resistance to extend components life
  - o Enhanced thermal and oxidation stability under high temperature, providing viscosity stability and preventing formation of deposits and sludge to prolong oil life

Provides excellent Driving Experience through:

- **Excellent low temperature viscosity** for improved lubrication during start-up in cold conditions

## Approvals, Specifications and Recommendations

PETRONAS Tutela Axle 500 is a high-quality, wide-range lubricant that meets and exceeds below performances:

### Approvals and Specifications:

- API GL-5
- MIL PRF 2105D

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your specific vehicle

## Typical Physical Data

Parameters	Method	Unit	Typical Value
Appearance	-	-	Bright & Clear
Density @15°C	ASTM D 4052	g/cm <sup>3</sup>	0.905
Kinematic Viscosity @100°C	ASTM D 445	mm <sup>2</sup> /s (cSt)	16.1
Viscosity Index	ASTM D 2270	-	160
Brookfield Viscosity @-40°C	ASTM D 2983	mPa.s (cP)	130000
Pour Point	ASTM D 97	°C	-42
Flash Point COC	ASTM D 92	°C	204

All technical data is provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: [www.pli-petronas.com](http://www.pli-petronas.com)

#### Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. (“**PLISB**”), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The data sheet and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 1693